


PCB Layout



㊲ With Mylar

Unless otherwise specified tolerance:

X.	± 0.50	X. °	± 3°
.X	± 0.38	.X °	± 2°
.XX	± 0.25		

Performance characteristics:

1.Main body part material

Insulator:LCP Black UL94V-0

Contact terminal: phosphor bronze,1.27~2μm Ni under plated,

Contact area plating Au 3 U" Min.,solder plating Sn 3~5μm.

2.Electrical requirements:

Current rating: 1.5 A

Voltage rating: 125 V

Contact resistance: ≤45 mΩ

Insulation resistance: ≥1000 MΩ

Withstanding voltage: 1000 Vr.m.s, 1mA, 60s

3.Environment specification

Working temperature: -45℃~85℃

Humidity: <93% at 40℃

4.Packing & storing



Method of packing: Tape&Reel ,Outer box

Storing condition: temperature of -10℃~+40℃  
below 80% relative humidity

5.Style of installation: SMT

6.To prevent the pollution of the environment product info

RoHS agreement: In line with the european union RoHS.

					RJ45 Connector 1*1 Without Shield Type 180° SMT	SL0. 1603. 003			
④	1	22712	An. Cheng	2015. 05. 05		Projection	Rev.	Weight	Scale
Mark	NO.	File NO.	Signature	Date			A1		
DRAW		An. Cheng 2014. 10. 27							
CHK									
MAN					All Dimensions in mm		Sheet 1 of 1		
STD					 SHINNING SHENZHEN SHINNING ELECTRONIC CO.,LTD.				
APP									