



Performance characteristics:

1. Main body part material

Insulator: PC, Clean UL94V-2

Contact terminal: Copper alloy, 1.27~2μm Ni under plated,
Contact Area Gold Flash.

2. Electrical requirements:

Current rating: 1.5 A

Voltage rating: 125 V

Contact resistance: <50 mΩ

Insulation resistance: >1000 MΩ

Withstanding voltage: 1000 Vr.m.s, 1mA, 60s

3. Environment specification

Working temperature: -40℃~80℃

Humidity: <93% at 40℃

4. Packing & storing

Method of packing: Plastic bag, inner box, outer box

Storing condition: temperature of -10℃~+40℃
below 80% relative humidity

5. Style of installation: Applicable for Press cable installation

6. To prevent the pollution of the environment product info

RoHS agreement: In line with the European Union RoHS.

| Part No. | Circuit |
|---------------|---------|
| 1611-026-01-F | 2 |
| 1611-046-01-F | 4 |
| 1611-066-01-F | 6 |

Unless otherwise specified tolerance:

| | | | |
|-----|-------|-----|-----|
| X. | ±0.50 | X.° | ±3° |
| .X | ±0.38 | .X° | ±2° |
| .XX | ±0.25 | | |

| | | | | | | | | |
|------|-----|----------|-----------|------------|---|------|--------|-------|
| | | | | | SL0. 1611. 001 | | | |
| | | | | | RJ11 Plug Connector | | | |
| Mark | NO. | File NO. | Signature | Date | Projection | Rev. | Weight | Scale |
| DRAW | | | An.Cheng | 2013-04-26 | | A0 | | |
| CHK | | | | | | | | |
| MAN | | | | | | | | |
| STD | | | | | | | | |
| APP | | | | | | | | |
| | | | | | 1611-XX6-01-F | | | |
| | | | | | All Dimensions in mm Sheet 1 of 1 | | | |
| | | | | | SHINNING SHENZHEN SHINNING ELECTRONIC CO., LTD. | | | |