

Unless otherwise specified tolerance:

X.	± 0.50	X. °	± 3°
.X	± 0.38	.X°	± 2°
.XX	± 0.25		

Performance characteristics:

1.Main body part material

Contact terminal: Phosphor bronze, 1.27 ~ 2μm Ni under plated, Contact Area Au0.76μm Min., Crimp Cable Area Sn 3 ~ 5μm.

2. Electrical requirements:

Current rating: 9 A

Voltage rating: 250 V

Contact resistance: ≤ 10 mΩ

3. Mechanical requirements

Wire gauge: AWG18 ~ 24

4. Environment specification

Working temperature: -25°C ~ +85°C

5. Packing & storing

Number of packing: 4500pcs/reel



Method of packing: Paper reel

Storing condition: temperature of -10°C ~ +40°C below 80% relative humidity

6. Style of installation: Applicable for crimp cable installation.

7. To prevent the pollution of the environment product info

RoHS agreement: In line with the European Union RoHS.

					4.20mm Wafer female terminal	SL0.1348.001			
						Projection	Rev.	Weight	Scale
Mark	NO.	File NO.	Signature	Date			A0		
DRAW	An.Cheng 2013-09-09								
CHK					13483002	All Dimensions in mm		Sheet 1 of 1	
MAN						 SHINNING SHENZHEN SHINNING ELECTRONIC CO.,LTD.			
STD									
APP									