



P. C. B LAYOUT  
TOP VIEW  
Tolerance:  $\pm 0.05$



#### Performance characteristics:

##### 1. Main body part material

Insulator: PA66+GF Natural UL94V-0

Contact terminal: Brass, 1.27~2  $\mu$ m Ni under plated,  
outer plating Sn 3~5  $\mu$ m

##### 2. Electrical requirements:

Current rating: 3A

Voltage rating: 250 V

Contact resistance:  $\leq 20$  m $\Omega$

Insulation resistance:  $\geq 1000$  M $\Omega$

Withstanding voltage: 800 Vr.m.s, 1mA, 60s

##### 3. Environment specification

Working temperature: -25 $^{\circ}$ C ~ 85 $^{\circ}$ C

Humidity:  $\leq 93\%$  at 40 $^{\circ}$ C

Resistance to soldering heat: 260 $^{\circ}$ C  $\pm$  5 $^{\circ}$ C, 10s

##### 4. Packing & storing

Method of packing: Plastic bag, small outer box

Storing condition: temperature of -10 $^{\circ}$ C ~ +40 $^{\circ}$ C  
below 80% relative humidity




##### 5. Style of installation: solder PCB installation.

##### 6. To prevent the pollution of the environment product info

RoHS agreement: In line with the european union RoHS.

Unless otherwise specified tolerance:

X.	$\pm 0.50$	X. $^{\circ}$	$\pm 3^{\circ}$
.X	$\pm 0.38$	.X $^{\circ}$	$\pm 2^{\circ}$
.XX	$\pm 0.25$		

					2.0mm Pitch Dual-Row wafer	SL0.1331.001				
						Projection		Rev.	Weight	Scale
Mark	NO.	File NO.	Signature	Date				A0		
DRAW	An.Cheng 2015.04.02									
CHK										
MAN										
STD					1331-123-1B-D	All Dimensions in mm		Sheet 1 of 1		
APP						 SHINNING SHENZHEN SHINNING ELECTRONIC CO.,LTD.				