



Performance characteristics:

1.Main body part material

Insulator: PA66 Nature UL94V-0

2.Electrical requirements:

Insulation resistance: $\geq 100 \text{ M}\Omega$

Withstanding voltage: 500 Vr.m.s, 1mA, 60s

3.Environment specification

Working temperature: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$

4.Packing & storing

Method of packing: Plastic bag, inner box, outer box

Storing condition: Temperature of $-10^{\circ}\text{C} \sim +40^{\circ}\text{C}$
below 80% relative humidity

5.Style of installation: Applicable for crimp cable installation

6.To prevent the pollution of the environment product info

RoHS agreement: In line with the european union RoHS.

Unless otherwise specified tolerance:

X.	± 0.50	X.°	$\pm 3^{\circ}$
.X	± 0.38	.X°	$\pm 2^{\circ}$
.XX	± 0.25		

Mark	NO.	File NO.	Signature	Date	1.25mm Pitch wafer female housing 8 Pin	SL0. 1341. 003			
DRAW						Projection	Rev.	Weight	Scale
CHK							A0		
MAN						All Dimensions in mm Sheet 1 of 1			
STD						13411017			
APP						SHINNING SHENZHEN SHINNING ELECTRONIC CO.,LTD.			